

**Patented &
Exclusive**

The CAM[®] Gauge Rake

by Midwest Rake Company, LLC

A "goof-proof" tool which applies a range of materials at a precise, specified, and uniform depth. For use in applying decorative concrete "toppings," self-leveling / high performance floor coating materials, and underlayments in the floor-covering markets. CAM[®] depth settings range from 1/32" to 1". A must have tool for the decorative concrete and floor coating contractor. **Frames and CAM[®] sets sold separately.**

Our Most Popular Sizes



1/8" - 57082




1/4" - 57084



3/8" - 57086

We use a "radial" edge CAM[®] design which maintains uniform coating thickness, even at varying handle angles and lengths.



24" frame with 66" handle
#57001

NEW

#57044

10" Hand-held CAM[®] Gauge Rake Frame.

CAM[®] sets sold separately.

#57000

24" frame with threaded handle adaptor



Milled threaded handle adaptor



1/32" - 57078



1/24" - 57079



1/16" - 57081



1/8" - 57082



3/16" - 57083



1/4" - 57084



5/16" - 57085



3/8" - 57086

1/2" CAM[®] Set
57088

1" CAM[®] Set
57096

Features

CAM[®] Gauge Rake Frames and CAM[®] Sets are sold separately

Head widths ranging from 10" (hand held... see image) to 48". The 24" and 36" widths are the most popular. CAM[®] sets, which are purchased separately, come in depth settings ranging from 1/32" to 1", with the 1/8", 1/4", 3/8" CAM[®] sets being the most popular (see image).

Each CAM[®] has multiple contact points of the same depth... When worn down, loosen the wing nut and rotate the CAM[®] for a fresh contact point of the same depth setting.

The CAM[®] Gauge Rake is available with a milled threaded handle adaptor (THA) or a 66" powder-coated aluminum handle (PCAH) and the 10" CAM[®] Rake used for small areas and counter tops has it's own a fixed handle with grip (see images).



P.O. Box 1674
Warsaw, Indiana 46581-1674
574-267-8508 Fax

Visit us at www.midwestrake.com
Call us at 1-800-815-7253